



Wet Look Floor Finish

PERFECT 610

PERFECT 610 is designed to achieve maximum gloss quickly and maintain it for extra-long periods of time. Each coat provides a clear, durable film for the protection of floor surface. The high solids, metal interlock system allows a floor to achieve beauty and protection rapidly without seal, thereby providing a savings in labor and material.

FLOOR PREPARATION - Floor must be clean and free of dirt, oils and debris. If stripping was necessary, ensure all old floor finish was removed prior to application of PERFECT 610.

APPLICATION - Use standard application procedures with thin to medium coats of finish. Make sure polish is completely dry before applying subsequent coat or opening to traffic. As long as the polish is allowed to completely dry between coats, as many coats as needed may be applied consecutively.

RECOAT - Scrub the floor with "GPC" cleaner and use a low speed buffer or automatic scrubber and blue or green (medium scrub) pads. Rinse the floor with clean water and let dry before applying PERFECT 610.

STRIPPING - If stripping is necessary, use DEMOLITION stripper according to label directions.

FEATURES

- Excellent Stain Resistance
- High solids formula
- Acrylic polymers stay clean, clear & shiny reducing maintenance
- Excellent water, soil and scuff resistance
- Excellent sealing properties – no separate sealer necessary
- Ideal for Low Maintenance (Non-Buff) programs
- Fast-drying – 20 to 30 minutes per coat under normal conditions

Item Number: RSG6205

PROPERTIES

Type	Metal-Interlocked Acrylic
Form.....	Opaque Liquid
Odor	Sweet
Color	Milky White
Film Clarity	Clear
Weight per Gallon	8.60 lbs.
pH.....	8.1 +/- 0.2
Floor Solids	27 %
Storage Stability	Min. 1 Year
Freeze/Thaw	Passes 3 Cycles
V.O.C.	<0.1% by weight
Slip Resistance	Exceeds ASTM D2047

RESOURCE SOLUTIONS, INC. warrants this product to be of consistent quality. RESOURCE SOLUTIONS, INC.'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product.