



## Green Floor Finish Zinc Free

# SUPER PROTECTOR 720

**SUPER PROTECTOR 720** creates a new standard in floor care by combining an unequalled level of environmental preference with performance, which surpasses conventional floor finish technology. Excels with all maintenance systems: scrub and recoat, spray buff or burnish. You'll get a tough, black-mark resistant shine with no powdering. No sealer is required on resilient flooring, even after heavy stripping. Use on vinyl, laminate, linoleum, rubber, brick, stone, terrazzo, and bamboo floors.

**FLOOR PREPARATION** - Remove all of the old finish using DEMOLITION Floor Stripper according to its directions. Rinse floor thoroughly to remove all residues and allow to dry.

**APPLICATION** - If unsealed, apply three thin coats of SUPER PROTECTOR 720 to build a maintainable base, allowing ~15 minutes drying time per coat (adjust as needed). For extra gloss and protection, apply two more thin coats. Thick coats require 24-48 hours to dry before reapplying.

**MAINTENANCE** - Dust mop daily to remove debris. Damp mop/autoscrub with ½ oz per gallon of Neutral Floor Cleaner. Burnish with an aqua pad for gloss restoration. Deep-scrub as needed to maintain shine.

## FEATURES

- Zinc-Free & Eco-Friendly – Safer for the environment and indoor air quality.
- Durable Protection – Provides a strong, long-lasting finish.
- High Gloss Finish – Enhances floor appearance with a polished look.
- Low Odor – Ideal for use in occupied spaces.
- Chemical Resistant – Alcohol, detergent and scuff resistant
- Easy Maintenance – Works with standard cleaning methods, including autoscrubbing and burnishing.
- Slip-Resistant – Helps improve safety in high-traffic areas.
- Fast-drying – 15 to 30 minutes per coat under normal conditions

**Item Number:** RSG72005

## PROPERTIES

Type .....	Zinc Free
Form.....	Opaque Liquid
Odor .....	No Odor
Color .....	Opaque White
Film Clarity .....	Clear
Weight per Gallon .....	8.60 lbs.
pH.....	7.95
Floor Solids .....	20 %
Storage Stability .....	Min. 1 Year
Freeze/Thaw .....	Passes 3 Cycles
V.O.C. ....	<0.1% by weight
Slip Resistance .....	Exceeds ASTM D2047

RESOURCE SOLUTIONS, INC. warrants this product to be of consistent quality. RESOURCE SOLUTIONS, INC.'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product.